安平县铂川丝网制品有限公司 ANPING BOCHUAN WIRE MESH CO.,LTD

EDEN.

安平县铂川丝网制品有限公司 ANPING BOCHUAN WIRE MESH CO..LTD

>>>勾花网

CHAIN LINK FENCE

>>>勾花网

CHAIN LINK FENCE

材料:优质低碳钢丝、不锈钢丝、铝合金丝、PVC丝。

编织及特点:钩编而成,网孔均匀、网面平整、美观大方、网幅宽,丝 径粗,不易腐蚀寿命长,编织简洁、美观实用。

用途:用处广泛,饲养鸡、鸭、鹅、兔及动物园围栏。机械设备的防护,高速公路护栏,体育场所围网,马路绿化带防护网。该丝网在制作成箱子状的容器后,用乱石等填满网箱,可用于保护和支持海堤、山坡、路桥、水库及其他土木工程。是防洪和抗洪上好材料。还可用于工艺品制造,机械设备的输送网。

丝径7#-20#孔径15'-1.5'特殊规格可根据客户需求加工订做。

Material: Low carbon steel wire, stainless steel wire, aluminum alloy wire, Pvc Coated Wire.

Weaving: Woven diamond pattern provides strong, durable and flexible construction. The closely spaced diamond mesh construction gives your fence linear strength and springy texture to protect horses from injury and prevent predators from entering paddocks and pastures

Uses: Chain Link Fence is used as fencing for sports field, river banks, construction and residence, also animal fencing.

Benefits: Low carbon steel dia Chain Link Fence has a heavy galvanized coating to ensure a long life.

The Chain Link Fence wire construction is:

strong;

safe and flexible;

does not break;

does not sag or roll up at the bottom.

















1."	1.5"	2"	2. 25	5" 2.	. 4"	2.5"	3"	4"		
25mm	40mm	50mm	55m	m 60	Omm	65mm	76mm	100mm		
18#-7#										
1. 20mm-5. 00mm										
1. On-50n										
				0, 5m-5. 0m						
4.11	1 5"	n"	2-1/4"	2-2/0"	2-1/0"	2-5/0"	0"	4"		
1	1.0		2-1/4	2-3/0				4		
	25mm	1" 1.5"	1" 1.5" 2"	1" 1.5" 2" 2-1/4"	25mm 40mm 50mm 55mm 60 18#-7# 1. 20mm-5. 00mm 1. 0m-50m 0. 5m-5. 0m 1" 1.5" 2" 2-1/4" 2-3/8"	25mm 40mm 50mm 55mm 60mm 18#-7# 1. 20mm-5. 00mm 1. 0m-50m 0. 5m-5. 0m 1" 1. 5" 2" 2-1/4" 2-3/8" 2-1/2"	25mm 40mm 50mm 55mm 60mm 65mm 18#-7# 1. 20mm-5. 00mm 1. 0m-50m 0. 5m-5. 0m 1" 1. 5" 2" 2-1/4" 2-3/8" 2-1/2" 2-5/8"	25mm 40mm 50mm 55mm 60mm 65mm 76mm 18#-7# 1. 20mm-5. 00mm 1. 0m-50m 0. 5m-5. 0m 1" 1. 5" 2" 2-1/4" 2-3/8" 2-1/2" 2-5/8" 3"		

Opening	1"	1.5"	2"	2-1/4"	2-3/8"	2-1/2"	2-5/8"	3"	4"
	25mm	40mm	50mm	57mm	60mm	64mm	67mm	75mm	100mm
Wire diameter	18#-13#			18#-7#					
	1.2-2	. 4mm		2. 0-5. 00mm					
Length of the roll				0.50	m-100m (or mo	re)			
Width of the roll	0. 5m-5. Om								
Ma	aterials and s	pecification	ns can be ma	de according	to customer	s' detailed r	equirements.		

• 05•